

PNOZ ml1p safe link 24VDC

773540



PNOZmulti Classic, link module, failsafe, connection between 2 base units, point-to-point, 32 Bit virtual inputs, 32 Bit virtual outputs.

Technical details

Certifications:	CE;cULus Listed;BG;EAC (Eurasian);TÜV;CCC;KCC
Number of safe virtual inputs:	32
Number of safe virtual outputs:	32
Max. data transmission time:	35 ms
Supply voltage (V):	24,0
Power consumption DC:	5.0 W
Version for extreme environ. conditions:	Standard
Width dimension:	22.5 mm
Height dimension:	94.0 mm
Depth dimension:	121.0 mm
Gross weight:	148 g
Net weight:	129 g
Ambient temperature:	0 - 60 °C

Accessories



783400










PNOZmulti Set spring loaded terminals




793400

PNOZ mi1p/mi2p/mo1p screw terminals

Optional accessories

	380000	SafetyNET p Cable per mtr
	773890	PNOZ mli1p 5m
	773891	PNOZ mli1p 10m screw
	773892	PNOZ mli1p 50m
	773893	PNOZ mli1p 5m
	773894	PNOZ mli1p 10m
	773895	PNOZ mli1p 50m
	773896	PNOZ mli1p 1,5m spring
	773897	PNOZ mli1p 1,5m screw



774639

KOP-XE



779110

PNOZmulti Bus-Terminator